

## Technical comparison of the Omnistor awnings

		5002	5102	5500	5800	6002	6502	6802	2000	Caravan style	9005	W-150
Installation	On the wall	+		+	+				+	+	+	+
	On the roof		+			+	+	+				
Installation pieces supplied as standard		+	+	+	+						+	+
Operation	Standard gear			+	+	+	+	+				
	Ultra fast gear	+	+									
	Automatic roller system								+			+
	Manual									+		
	Only with motor										+	
Clips for stowing the crank handle		+		+	+	+	+	+	not applicable	not applicable	not applicable	not applicable
Motor possible		+		+	+	+	+	+				
Dimensions (without motor)	Maximum length	4,00m	2,60m	6,00m	5,00m	3,75m	5,50m	5,00m	3,00m	4,50m	6,30m	2,85m
	Maximum projection*	2,50m	2,00m	2,50m	2,75m	2,50m	2,50m	2,75m	2,15m	2,30m	2,45m	0,64m
	Minimum weight	14 kg	19,8 kg	35,5 kg	28 kg	22,4 kg	36,5 kg	32 kg	11 kg	7,5 kg	39,5 kg	3,9 kg
	Maximum weight	27 kg	19,8 kg	52 kg	46,5 kg	31,2 kg	49 kg	45,5 kg	17,5 kg	14,5 kg	53,6 kg	8,7 kg
Arms	Retractable arms	+	+	+	+	+	+	+				
	Telescopic arms								+			
	Tension arms									+		
	Scissor arms										+	
	Projection arms											+
Quick-Lock system		+	+	+	+	+	+	+	+	+	not applicable	not applicable
Wall brackets supplied as standard		+		+	+	+	+	+	+	+	not applicable	not applicable
Safari-Room possible		+		+	+	+	+	+	+			
Rain-blocker side possible		+		+					(!)	+		
Sun-blocker side possible		+		+		+	+					
Sun- or Rain-blocker possible		+	+	+	+	+	+	+	+	+		
Suitable for small vehicles									+	+		

\* remark: the maximum projection is only possible in combination with greater lengths. Please consult the technical specifications for more information.

(!) only for VWT4