

Technical comparison of the Omnistor awnings

		8000	5003	5002	5102	5500	5800	6002	6502	6802	6900	2000	Caravan style	W-150
Installation	On the wall	+	+	+		+	+					+	+	+
	On the roof				+			+	+	+	+			
Installation pieces supplied as standard		+		+	+	+	+							+
Operation	Standard gear					+	+	+	+	+				
	Ultra fast gear	+	+	+	+						+			
	Automatic roller system											+		+
	Manual												+	
Only with motor														
Clips for stowing the crank handle		+	+	+		+	+	+	+	+	+	not applicable	not applicable	not applicable
Motor	possible	+		+		+	+	+	+	+	+			
	retro fit possible	+												
	with remote control	+												
Dimensions (without motor)	Maximum length	6,03m	4,55m	4,00m	2,60m	6,00m	5,00m	3,75m	5,50m	5,00m	5,50m	3,00m	4,50m	2,85m
	Maximum projection*	2,75m	2,50m	2,50m	2,00m	2,50m	2,75m	2,50m	2,50m	2,75m	2,75m	2,15m	2,30m	0,64m
	Minimum weight	38,0kg	15kg	14 kg	19,8 kg	35,5 kg	28 kg	22,4 kg	36,5 kg	32 kg	36,5kg	11 kg	7,5 kg	3,9 kg
	Maximum weight	55,4kg	33,2kg	27 kg	19,8 kg	52 kg	46,5 kg	31,2 kg	49 kg	45,5 kg	49kg	17,5 kg	14,5 kg	8,7 kg
Arms	Retractable arms	+	+	+	+	+	+	+	+	+	+			
	Telescopic arms											+		
	Tension arms												+	
	Scissor arms													
	Projection arms													+
Integrated tension arm		+												
Quick-Lock system		+	+	+	+	+	+	+	+	+	+	+	+	not applicable
Wall brackets supplied as standard		+	+	+		+	+	+	+	+	+	+	+	not applicable
Safari-Room possible				+		+	+	+	+	+		+		
Safari-Residence possible		+	+	+		+	+	+	+	+	+	+		
Rain-blocker side possible		+	+	+		+					+	(!)	+	
Sun-blocker side possible		+	+	+		+		+	+		+			
Sun- or Rain-blocker possible		+	+	+	+	+	+	+	+	+	+	+	+	
Suitable for small vehicles												+	+	

* remark: the maximum projection is only possible in combination with greater lengths. Please consult the technical specifications for more information.

(!) only for VWT4